



FIREX

THE ESSENTIAL SERVICES SUPPLIER

WHEN YOU WANT, WHERE YOU WANT

IT'S THE FIREX DIFFERENCE

1300 246 247

WWW.FIREX.COM.AU



Fire-Lite Product List

SAP PART #	DESCRIPTION
* SERIES CONVENTIONAL PANEL	
LST-816/650-8Z-PS5	LST816– 8 zones fitted with NPS-5 in CAB650, 5.6A PSU
LST-816/650-8ZPS11	LST816 - 8 zones fitted with NPS-11 in CAB650, 11.7A PSU
LST-816/900-8ZPS11	LST816 - 8 zones fitted with NPS-11 in CAB900, 11.7A PSU
* ACCESSORIES	
ZEM-8	8 Zone expansion module
ZLKT16	Zone label kit, 16 zones, 1 x Annunciator
ACM-ZM8	Remote LED mimic annunciator for up to 8 zones
AEM-ZM8	Remote LED mimic expansion annunciator for up to an additional 8 zones
IFS-993F	Monitored Strobe/Sounder driver card. 5 Amp fused reversing output + fault output
FIRELITE SMX+ FIRE ALARM CONTROL PANEL	
SMX+650-1L-PS5	SMX+ in CAB650 with 1xSLC, NPS-5
SMX+650-1L-PS11	SMX+ in CAB650 with 1xSLC, NPS-11
SMX+900-1L-PS5	SMX+ in CAB900 with 1xSLC, NPS-5
SMX+900-1L-PS11	SMX+ in CAB900 with 1xSLC, NPS-11
SMX+ EXPANSION MODULES	
LCM-320	Loop Control Module
LEM-320	Loop Expander Module
ACM-8RA	Relay module to provide up to 8 C/NO/NC relay contacts
NETWORK CONTROL ANNUNCIATOR NCA	
SMX+NCA2	SMX+ Network Control Annunciator, requires DISP-SMX+
SMX+ ANNUNCIATORS	
LCD2-80-AUS	LCD Annunciator (80 Character), to suit SMX+/NCA-2
SCS-8A	Smoke Control Annunciator (Control) 8 x switch groups
SCE-8A	Smoke Control Annunciator (Expander) 8 x switch groups
SCS-8L	Smoke Control Lamp Driver Kit 8 x switch groups
SCE-8L	Smoke Control Lamp Driver (Expander) to suit AFP-3030
ACM-24AT-AUS	Annunciator Control 24 buttons, 48 LEDs
AEM-24AT-AUS	Annunciator Expander 24 buttons,48 LEDs
ACM-48A-AUS	Annunciator Control, 48 LEDs, to suit AFP-3030/NCA-2
AEM-48A-AUS	Annunciator Expander, 48 LEDs, to suit AFP-3030/NCA-2
LDM-32-AUS	Lamp Driver Module (Control), 32 LEDs or LDM-R32
LDM-E32-AUS	Lamp Driver Module (Expander), 32 LEDs or LDM-R32
LDM-R32-AUS	Lamp Driver Relay Kit, 32 Relay board, requires LDM-32

SAP PART #	DESCRIPTION
SMX+ NETWORKING MODULES	
NCM-W	Network Control Module (Wire)
NCM-F	Network Control Module - Multi-mode optical fibre
RPT-WF	Not-Fire-Net network wire to multi-mode fibre repeater
RPT-W	Noti-Fire-Net network wire to wire repeater
SMX+ ACCESSORIES	
USB3	USB programming lead 3m, USB type A to type B
ARE EQUIPMENT MOUNTING BRACKETS	
ARE	ARE Interface Board Assembly to suit custom jobs
ARE-T	ARE interface to suit Centaur
ARE-CR	ARE interface to suit Code Red, Almos (shallow)
ARE-R	ARE interface to suit Romteck, Almos and Centaur II
SMOKE ALARMS	
2012/24AUSI	12/24VDC 4-wire smoke alarm with 9V battery backup - AS3786
2012J	12/24VDC 4-wire smoke alarm (no batt back-up)
CONVENTIONAL DETECTORS	
2151BAUS	Conventional Photo Optical Smoke detector, 7%/m obscuration, uses B401 AUS Base
5151AUS	Conventional Thermal Detector, Fixed Temp 63deg, System Sensor, requires B401 AUS
5151HAUS	Conventional Thermal Detector, Fixed Temp 90deg, System Sensor, requires B401 AUS
5151RAUS	Conventional Thermal Detector, Rate of Rise, 63deg, System Sensor, requires B401 AUS
5151RHAUS	Conventional Thermal Detector, Rate of Rise, 90deg, System Sensor, requires B401 AUS
885-WP	Conventional Sealed Thermal, 60deg ROR, inc flying leads and mounting base
B401AUS	Universal base for System Sensor 100 Series conventional detectors
D2-AUS	Conventional 2-wire duct detector (inc detector, requires sampling tube)
D4120	Photo Duct detector 4-wire (24VDC, 24VAC, 120VAC)
D4120W	4-Wire watertight duct detector (24VDC, 24VAC, 120VAC)
OSI-R-SS	OSID-R System Sensor Conventional Beam Detector
DST1.5	Duct Sampling Tube, 45cm, to suit duct 0.3m to 0.6m
DST3	Duct Sampling Tube, 90cm, to suit duct 0.5m to 1.2m
DST5	Duct Sampling Tube, 1.5m, to suit duct 1.2m to 2.4m
DST10	Duct Sampling Tube, 3m, to suit duct 2.4m to 3.7m
BEAMSMK	Surface Mount Kit for BEAM 1224 for flat surfaces only
BEAMLRK	Long Range Kit for BEAM 1224
BEAMMMK	Multi Mounting Kit Reflective for BEAM 1224 - when mounting beam on an angle. Requires BEAMSMK surface mount kit.
RTS151KEY	Key switch for BEAM 1224S

SAP PART #	DESCRIPTION
E60-AUS	E-Type Heat Detector Probe set at 60degC
E65-AUS	E-Type Heat Detector Probe set at 65degC
E70-AUS	E-Type Heat Detector Probe set at 70degC
E80-AUS	E-Type Heat Detector Probe set at 80degC
E90-AUS	E-Type Heat Detector Probe set at 90degC
E100-AUS	E-Type Heat Detector Probe set at 100degC
E110-AUS	E-Type Heat Detector Probe set at 110degC
E120-AUS	E-Type Heat Detector Probe set at 120degC
E150-AUS	E-Type Heat Detector Probe set at 150degC
E180-AUS	E-Type Heat Detector Probe set at 180degC
E200-AUS	E-Type Heat Detector Probe set at 200degC
E240-AUS	E-Type Heat Detector Probe set at 240degC
ADDRESSABLE DETECTORS - CLIP PROTOCOL	
2351BAUS	Intelligent Photo-Optical Smoke Detector, System Sensor
2351TBAUS	Intelligent Photo-Optical & Thermal Detector, System Sensor
2351PTIR AUS	Intelligent Photo, Thermal and IR Multi-Criteria Detector, System Sensor
5351BAUS	Intelligent Fixed Temperature Thermal detector, System Sensor
5351RBAUS	Intelligent Rate-of-Rise Thermal detector, System Sensor
5351HAUS	Intelligent High Temperature Fixed Thermal detector, System Sensor
7351AUS	Intelligent High Sensitivity Detector, System Sensor
5251B-WP	Intelligent SS Weatherproof Fixed temp Thermal Sensor, Off-White, CLIP
5251RB-WP	Intelligent SS Weatherproof ROR Thermal Sensor, Off-White, CLIP
OSI-RI-SS	OSID-R System Sensor Clip Intelligent
DETECTOR ACCESSORIES	
B501AUS-IV	Universal addressable detector base, off white
B501AUS-W	Universal addressable detector base, pure white, System Sensor
B501AUS-BK	Black Detector base for addressable detectors
B501BI-W	Isolator Base - Bright white to suit addressable detector
B501BI-IV	Isolator Base - Ivory to suit addressable detector
B501BI-BL	Isolator Base - Black to suit addressable detector
CP500	Addressable Detector Programmer, to suit Weatherproof thermal detectors
DNR-AUS	Duct detector housing for intelligent photoelectric detectors, requires detector and sampling tube
DNRW	Weatherproof duct detector housing, requires detector and sampling tube
BEAMSMK	Surface Mount Kit for BEAM 1224 for flat surfaces only, built in test
BEAMLRK	Long Range Kit for BEAM 1224
BEAMMMK	Multi Mounting Kit Reflective for BEAM 1224 - when mounting beam on an angle. Requires BEAMSMK surface mount kit.

SAP PART #	DESCRIPTION
RTS151KEY	Key switch for BEAM 1224S
DETSS	Stainless steel detector guard square
STI-8100	Polycarbonate Detector Guard, flushmount
STI-9604	White wire detector guard, flushmount
DETBKT-1	Concealed Detector Bracket - 1m
DETBKT-2	Concealed Detector Bracket - 2m
DETBKT-3	Concealed Detector Bracket - 3m
REMOTE INDICATORS	
RI-CON	Remote Indicator "FIRE ALARM - IN CONCEALED SPACE"
RI-FLOOR	Remote Indicator "FIRE ALARM - UNDER FLOOR"
RI-LIFT	Remote Indicator "FIRE ALARM - IN LIFT SHAFT"
RI-ROOF	Remote Indicator "FIRE ALARM - IN ROOF"
RI-ROOM	Remote Indicator "FIRE ALARM - IN ROOM"
ADDRESSABLE FIELD INPUT & OUTPUT MODULES	
M500DMR	Addressable Dual Input/Dual Output module, CLIP, System Sensor
M200E-DIN	DIN rail mounting bracket, to suit Euro style modules
M200E-PMB	Panel mounting bracket, to suit Euro style modules
M200E-SMB-KO	Surface mount enclosure, to suit Euro style modules
M500M	Addressable input module, CLIP, System Sensor
M500R	Addressable relay output module, CLIP, System Sensor
M500S	Addressable Control Module, CLIP Supervised, System Sensor
M501M	Addressable mini input module, CLIP, System Sensor
M502M	Addressable zone input module, CLIP, System Sensor
M500X	Addressable Isolator module, CLIP, System Sensor
SMB500	Surface Mounting Box - 500 series, to suit addressable modules
AAM/LP/HL	Alarm Acknowledgement Module, horizontal orientation with LED
AAM/LP/V	Alarm Acknowledgement Module
AAM/LP/VL	Alarm Acknowledgement Module, vertical orientation with LED
ADDRESSABLE FIELD INPUT & OUTPUT MULTI-MODULES	
XP6-MA	Addressable multi-module 6 way zone interface module. Requires 24V, Requires mounting metalwork or DGP
CR-6	Multi-module, 6x Relay Outputs - System Sensor, Requires mounting metalwork or DGP
IM-10	Multi-module, 10 inputs - System Sensor, Requires mounting metalwork or DGP
SC-6	Multi-module 6x Monitored Relays, Requires mounting metalwork or DGP

SAP PART #	DESCRIPTION
ADDRESSABLE LOOP POWERED AUDIO-VISUAL ALARM DEVICES (AAD & VAD'S)	
BSO-LASS-NCW	Addressable Sounder Base - Pure white, System Sensor, CLIP (requires B501-W base)
WSO-PP-N46	Addressable Wall Sounder - White, System Sensor, CLIP
WSO-PR-N46	Addressable Wall Sounder - Red, System Sensor, CLIP
VAD-PC-100	SS Pure White Clear Strobe "w Isolator, AS7240.23 (C-3-5.1)
WSS-PC-101	Pure White Sounder Strobe Clear w Isolator, AS7240.23 O Category
B501AP-W	Base to suit loop-powered AV, pure white
WPW	Waterproof AV-device base, pure white for addressable AV range
BRR	Deep base (Red), to suit addressable AV
WRR	Waterproof base (Red) to suit addressable AV
EMERGENCY WARDEN INTERCOM PHONE (WIP)	
WIP	Warden Intercommunication Phone (WIP) Handset
DA2 SERIES VOICE ALARM MODULES - AS4428.16	
DA2-30	30 Watt Digital building occupant warning system
DA2-60	60 Watt Digital building occupant warning system
DA2-120	120Watt Digital building occupant warning system
SAM-4	Speaker amplifier monitoring and distribution module with 4 monitored speaker lines
DA-DISPF	DA Preamp and PA microphone c/w with light grey metalwork for one slot to suit BC-200
CMM-2	Custom message module c/w PC connect audio cable (2x messages)
DA SERIES VOICE ALARM MODULES	
DA-30CAB	Stand-alone DA-30 with NPS-5 in CAB650
DA-60CAB	Stand-alone DA-60 with NPS-11 in CAB650
DA-120CAB	Stand-alone DA-120 with NPS-11 in CAB650
DA-DISPA	Display and PA microphone module for DA-BOWS to suit 18u/28u/40u cabinet
DA-DISPB	Display and PA microphone module for DA-BOWS to suit CAB650/900
DA-DISPC	Display module for DA-BOWS to suit 18u/28u/40u cabinet
DA-DISPD	PA selector module for up to 4 PA zones using DA-BOWS
SDM-4	4 way speaker distribution module c/w EOLs, screws, stand-offs

SAP PART #	DESCRIPTION
LEADWAY AS7240.24 VOICE ALARM SPEAKERS	
L-VCP06D-W	4" Ceiling Loudspeaker, 6/3/1.5/0.75/0.375W, White 100mm
L-VCP06D-W	4" Ceiling Loudspeaker, 6/3/1.5/0.75/0.375W, White 100mm
L-VCP06D-BK	4" Ceiling Loudspeaker, 6/3/1.5/0.75/0.375W, Black 100mm
L-SMB-W	Surface Mount Box, White
L-SMB-BK	Surface Mount Box, Black
L-VWM06A/ENC	4" Metal wall mount loudspeaker, 6/3/1.5/0.75w, white metal enclosure, with capacitor
L-VCP06A/ENC	5" Ceiling Speaker, AS7240.24 with Plastic Fire Dome, White, 6w/3w/1.5w
L-VCM6B/ENC	5" Metal ceiling loudspeaker, 6/3/1.5/0.75w, red fire dome, with capacitor
L-VCM6A/ENC	6.5" Metal ceiling loudspeaker, 6/3/1.5/0.75w, red fire dome, with capacitor
L-VCM24A/EN(SAI)	6.5" Metal coaxial ceiling loudspeaker, 24/12/6/3W,4ohm, red fire dome
	Outdoor horn,15/10/5W,8ohm, Grey , ABS, with capacitor
L-VJP15A/EN-W	15W Unidirect. Projection Speak.AS7240.24 c/w capacitor, White, 15/7.5/3.75/1.9/0.95W
L-VJP15A/EN-BK	15W Unidirect. Projection Speak.AS7240.24 c/w capacitor, White, 15/7.5/3.75/1.9/0.95W
L-VJM10A/ENC	Unidirectional speaker,10/5/2.5/1.25W,White , Aluminium ,with capacitor
L-VJM20A/ENC	Unidirectional projection loudspeaker, 20/10/5/2.5W, White, Aluminium, with capacitor
L-VBM20A/ENC	Bidirectional speaker, 20/10/5/2.5W, White, Aluminium, with capacitor
L-VOM20A/ENC	Outdoor column speaker, 20/10/5/2.5W, White, Aluminium, with capacitor
L-VOM40A/ENC	Outdoor column speaker, 40/20/10/5W, White, Aluminium, with capacitor
HOLES AW-140	140mm Hole Saw with Arbor, to suit L-VCP06D / SP-100

SAP PART #	DESCRIPTION
ENSCAPE CONVENTIONAL AUDIO VISUAL ALARM DEVICES - AS7240.3 / AS7240.23	
CWSO-RR-S1	Surface mount sounder. Red, low profile base
CWSO-WW-S1	Surface mount sounder. White low profile base
CWSO-RR-W1	Surface mount IP65 sounder. Red
CWSO-WW-W1	Surface mount IP65 sounder. Red
CWST-RR-S5	Surface mount strobe, red body, red flash, clear lens, low profile base
CWST-RW-S5	Surface mount strobe, red body, white flash, clear lens, low profile base
CWST-WR-S5	Surface mount strobe, wh body, red flash, clear lens, low profile base
CWST-WW-S5	Surface mount Strobe wh body, white flash, clear lens, low profile base
CWST-RR-W5	Surface mount Strobe IP65 base, red body, clear lens, red flash
CWST-RW-W5	Surface mount Strobe IP65 base, red body, clear lens, white flash
CWST-WR-W5	Surface mount Strobe IP65 base, wh body, clear lens, red flash
CWST-WW-W5	Surface mount Strobe IP65 base, wh body, clear lens, white flash
CWSS-RR-S5	Surface mount Sound/Strobe, red body, clear lens, red flash
CWSS-RW-S5	Surface mount Sound/Strobe, red body , clear lens, white flash
CWSS-WR-S5	Surface mount Sound/Strobe, wh body, clear lens, red flash
CWSS-WW-S5	Surface mount Sound/Strobe, wh body, clear lens, white flash
CWSS-RR-W5	Sounder/Strobe IP65 base, red body, clear lens, red flash, Surface mount
CWSS-RW-W5	Sounder/Strobe IP65 base, red body, clear lens, white flash, Surface mount
CWSS-WW-W5	Sounder/Strobe IP65 base, white body, clear lens, white flash, Surface mount
STR-DUAL	Red/Amber Dual Strobe on white metal box - 100mA 24V
SRHKRLFIRE	Strobe, Red 135 - 185 Candela. Labelled "Fire"
FIRE ALARM BELLS	
SSM12-6	6" (150mm) Fire Alarm bell - 12VDC
SSM24-6	6" (150mm) Fire Alarm bell - 24VDC
SSM24-8	8" (200mm) Fire Alarm bell - 24VDC
WBB	Back Box to suit Fire Allarm Bells -Red

SAP PART #	DESCRIPTION
CONVENTIONAL MANUAL CALL POINTS (MCP)	
M1A-R470SG-STCK-01	Red Surface mount MCP, House + Flame, back box included
M3A-R000SF-STCK-01	Red resettable Surface mount MCP
M3A-W000SG-K013-20	White surface mount MCP "EVACUATE"
M3A-Y000SG-STCK-11	Yellow Surface mount MCP, no label
M3A-G000SG-STCK-12	Green Surface mount MCP "Door Release"
M3A-B000SG-K013-11	Blue Surface mount MCP, no label
M4A-W000SF-K013-12	Resettable White Double pole indoor MCP, Emergency door release
M4A-G000SF-K013-11	Resettable Green Double pole MCP , for Emergency door release
W3A-R000SG-STCK-01	Red outdoor IP67 Surface mount MCP , House + Flame
W3A-W000SG-K013-11	White outdoor IP67 Surface mount MCP, Plain
W3A-Y000SG-K013-54	Yellow outdoor IP67 Surface mount MCP, "Extinguishant Release"
W3A-G000SG-STCK-12	Green outdoor IP67 Surface mount MCP, "Emergency Door Release"
W3A-B000SG-K013-11	Blue outdoor IP67 Surface mount MCP, no label
W4A-G000SG-K013-12	Green Double pole outdoor IP67 MCP , with glass element
ADDRESSABLE MANUAL CALL POINTS (MCP)	
M5A-RP01SF-K013-01	Address CLIP Indoor MCP House&Flame with flexible element, requires clear flap and back box.
W5A-RP01SG-K013-01	Red CLIP MCP surface, IP67, House+Flame requires SR, c/w flex-element, clear flap
MANUAL CALL POINT ACCESSORIES	
SG-1x10	Spare glass (pk 10), common to all MCPs
PS200	Replacement clear flap to suit all other KAC MCP's
PS210	Flexible MCP element to suit KAC MCP's
SC070	Spare test key to suit all MCPs (pk10)
MUS041W	Back box suitable for surface mounting KAC Manual Call Point
STI-1130	Indoor Protective Stopper with Horn and Clear Spacer c/w Fire Label
STI-3150	Weather stopper, clear polycarbonate enclosure
MAGNETIC DOOR HOLDERS	
MDH400	Magnetic Door Holder 400N (41kg)
MDH1000	Magnetic Door Holder 1000N (102kg)
MDH/F	Magnetic Door Holder Floor mount bracket
MDH/W15	Magnetic Door Holder Wall mount bracket 15cm arm
MDH/W30	Magnetic Door Holder Wall mount bracket 30cm arm
MDH400/15	Magnetic Door Holder 400N (41kg), 15cm arm
MDH400/30	Magnetic Door Holder 400N (41kg), 30cm arm
SZ2575	Magnetic Door Holder Surface mount box for MDH400/15 or MDH400/30
MDHREM	Magnetic Door Holder remote release plate - flush mount

SAP PART #	DESCRIPTION
FLAME DETECTORS	
FSL100-UV	UV flame detector Suitable for ATEX zone 2/22; FM 3611 Class 1, 2 & 3 Div2 EN54-10 (HIGH sensitivity) certificate FM3260 approval (pending*). Red Housing
FSL100-UV-W	FSL100-UV-W - UV flame detector Suitable for ATEX zone 2/22; FM 3611 Class 1, 2 & 3 Div2 EN54-10 (HIGH sensitivity) certificate FM3260 approval (pending*). White Housing
FSL100-UVIR	UV/IR flame detector Suitable for ATEX zone 2/22; FM 3611 Class 1,2 & 3 Div2 EN54-10 (HIGH sensitivity) certificate FM3260 approval (pending*). Red Housing
FSL100-UVIR-W	UV/IR flame detector Suitable for ATEX zone 2/22; FM 3611 Class 1,2 & 3 Div2 EN54-10 (HIGH sensitivity) certificate FM3260 approval (pending*). White Housing
FSL100-IR3-W	Triple IR flame detector Suitable for ATEX zone 2/22; FM 3611 Class 1,2 & 3 Div2 EN54-10 (HIGH sensitivity) certificate (pending*) FM3260 approval (pending*). Red Housing
FSL100-IR3-W	Triple IR flame detector Suitable for ATEX zone 2/22; FM 3611 Class 1, 2 & 3 Div2 EN54-10 (HIGH sensitivity) certificate (pending*) FM3260 approval (pending*). White Housing
FSL100-SM21	FSL100 Optional swivel mount
FSL100-TL	FSL Test lamp

SAP PART #	DESCRIPTION
LINEAR HEAT DETECTION	
SS-LD-68-155-100	Linear Heat Cable 68deg, 100m roll
SS-LD-68-155-200	Linear Heat Cable 68deg, 200m roll
SS-LD-68-155-500	Linear Heat Cable 68deg, 500m roll
SS-LD-68-155-1000	Linear Heat Cable 68deg, 1000m roll
SS-LD-78-172-100	Linear Heat Cable 78deg, 100m roll
SS-LD-78-172-200	Linear Heat Cable 78deg, 200m roll
SS-LD-78-172-500	Linear Heat Cable 78deg, 500m roll
SS-LD-78-172-1000	Linear Heat Cable 78deg, 1000m roll
SS-LD-88-190-100	Linear Heat Cable 88deg, 100m roll
SS-LD-88-190-200	Linear Heat Cable 88deg, 200m roll
SS-LD-88-190-500	Linear Heat Cable 88deg, 500m roll
SS-LD-88-190-1000	Linear Heat Cable 88deg, 1000m roll
SS-LD-105-220-100	Linear Heat Cable 105deg, 100m roll
SS-LD-105-220-200	Linear Heat Cable 105deg, 200m roll
SS-LD-105-220-500	Linear Heat Cable 105deg, 500m roll
SS-LD-105-220-1000	Linear Heat Cable 105deg, 1000m roll
SS-LDN-68-155-100	Linear Heat Cable 68deg, w Nylon Coating, 100m roll
SS-LDN-68-155-200	Linear Heat Cable 68deg, w Nylon Coating, 200m roll
SS-LDN-68-155-500	Linear Heat Cable 68deg, w Nylon Coating, 500m roll
SS-LDN-68-155-1000	Linear Heat Cable 68deg, w Nylon Coating, 1000m roll
SS-LDN-78-172-100	Linear Heat Cable 78deg, w Nylon Coating, 100m roll
SS-LDN-78-172-200	Linear Heat Cable 78deg, w Nylon Coating, 200m roll
SS-LDN-78-172-500	Linear Heat Cable 78deg, w Nylon Coating, 500m roll
SS-LDN-78-172-1000	Linear Heat Cable 78deg, w Nylon Coating, 1000m roll
SS-LDN-88-190-100	Linear Heat Cable 88deg, w Nylon Coating, 100m roll
SS-LDN-88-190-200	Linear Heat Cable 88deg, w Nylon Coating, 200m roll
SS-LDN-88-190-500	Linear Heat Cable 88deg, w Nylon Coating, 500m roll
SS-LDN-88-190-1000	Linear Heat Cable 88deg, w Nylon Coating, 1000m roll
SS-LDN-105-220-100	Linear Heat Cable 105deg, w Nylon Coating, 100m roll
SS-LDN-105-220-200	Linear Heat Cable 105deg, w Nylon Coating, 200m roll
SS-LDN-105-220-500	Linear Heat Cable 105deg, w Nylon Coating, 500m roll
SS-LDN105-220-1000	Linear Heat Cable 105deg, w Nylon Coating, 1000m roll
8687/EOL	47k End of Line Box
MB	LHD Junction Box

SAP PART #	DESCRIPTION
POWER SUPPLIES	
HLSPS25	2.5 Amp PSU in Dark Grey Cabinet Stand-Alone PSU AS7240.4
HLSPS50	5 Amp PSU in Dark Grey Cabinet Stand-Alone PSU AS7240.4
NPS-DISP	Display kit for NPS power supplies, provides indication and battery test switch
BATTERIES	
BATT7	SLA Battery 7AH - 151mm (L) x 65mm (W) x 101mm (H)
BATT12	SLA Battery 12AH - 151mm(L) x 98mm(W) x 101mm(H)
BATT18	SLA Battery 18AH - 181mm(L) x 77mm(W) x 167mm(H)
BATT22	22AH 12V SLA Battery , 181mm(l)x77mm(w)x167mm(h)
BATT26	SLA Battery 26AH - 175mm(L) x 166mm(W) x 125mm(H)
BATT33	SLA Battery 33AH - 195mm(L) x 130mm(W) x 180mm (H)
BATT40	SLA Battery 40AH - 197mm(L) x 165mm(W) x 170mm(H)
BATT75	SLA Battery 75AH - 258mm(L) x 166mm(W) x 206mm(H)
BATT85	SLA Battery 85AH - 305mm(L) x 168mm(W) x 212mm(H)
BATT100	SLA Battery 100AH - 330mm(L) x 172mm(W) x 221mm(H)
BATT150	SLA Battery 150AH - 485mm(L) x 172mm(W) x 240mm(H)
SOLO TEST KITS	
SOLO911-001	SOLO 365 Detector Test Starter Pack to 6 metres Smoke Adv. Kit
SOLO365-001	SOLO 365 Detector Smoke Test Kit
SOLO372-001	SOLO 365 Detector Test ASD Adapter
SOLO808-001	Smoke detector test starter kit to 4m
SOLO809-001	Smoke detector test starter kit to 6m
SOLO811-001	Smoke Detector Test & Removal Set to 6m
SOLO814-001	Smoke / Heat detector test kit 240v mains powered to 6m
SOLO822-001	Smoke/Heat detector test kit Battery powered to 6m
SOLO823-001	Smoke/Heat detector test kit Battery powered to 9.3m
SOLO100-001	4.5m extension pole Fibreglass, telescopic
SOLO108-001	2.5m extension pole Fibreglass, telescopic
SOLO101-001	Fibreglass Extension Pole – 1.13metres
SOLO200-001	Universal Detector Removal Tool
SOLO330-001	Smoke and CO dispenser (Smoke / CO detector cup)
SOLO460-001	Cordless Heat Tester (Head only)
SOLO461-001	Cordless Heat Detector Test Kit battery powered inc charger
SOLO424-001	Heat tester 240V
SOLO425-001	Extension cable 5m for use with the SOLO424
SOLO610-001	Protective Carrying / Storage Bag
SOLO770-001	Replacement Battery Baton for use with the SOLO461
SOLO726-001	Battery charger to suit heat tester (compatible with battery batons Solo720 / Solo760)

SAP PART #	DESCRIPTION
SOLO727-001	Battery charger to suit heat tester (compatible with battery batons Solo720 / Solo760 / Solo770)
SOLO AEROSOLS	
SOLOA10-001	Test Smoke 150ml Non-Flammable HCF-Free (use with dispenser)
SOLOA5-001	Test Smoke 250ml Flammable HCF-Free, hand-held or dispenser use
SOLOC3-001	Test CO 250ml, use With Dispenser
SMOKESABRE-01-00	Smoke detector tester with retractable 'funnel', 150ml
TESTING & MEASUREMENT EQUIPMENT	
SMOKEPEN	Smoke Pen and refills - c/w 6 x refills
SMOKEPEN-R	Smoke Pen Refills - c/w 6 refills
M02-09-00	System Sensor telescopic test magnet
SENS-RDR	Sensitivity Reader for 2151BAUS
IMP-METER	Digital Impedance Meter, 9V Battery, LCD Display
ENCLOSURES - BATTERY BOXES	
DGP1B	Metal mounting box for 2 x XP modules
DGP2B	Metal mounting box for 4 x XP modules
MOUNTING CHASSIS & BRACKETS	
CHS-2	Mounting chassis for up to 2 x XP modules (1 slot)
CHS-4AUS	Mounting chassis for up to 4 x XP modules
CHS-6	Mounting chassis for up to 6 x XP modules (3 slots)
CHS-1L	Mounting chassis to suit 1 x LCM/ DA-BOWS with Cable Tie Mounts
CHS-2L	Mounting chassis to suit 2 x LCM/ DA-BOWS with Cable Tie Mounts
CHS-4L	Mounting chassis to suit 4 x LCM/ DA-BOWS with Cable Tie Mounts
ASE-CR	ASE bracket to suit Code Red, Almos (shallow)
ASE-R	ASE bracket to suit Romteck, Almos and Centaur II
ASE-T	ASE bracket to suit Centaur
SURGE SUPPRESSION MODULES	
SURGE-MAINS	Surge suppression and line filter for 240V mains (10A max)
SURGE-AZF	Surge suppression for 4 x AZF (conventional zone) circuits
SURGE-SLC	Surge suppression for SLC loop. Protects both A & B channels
SURGE-RS485	Surge suppression for RS485 communications
SURGE-24V	Surge suppression for 24V circuits, 2 channel

SAP PART #	DESCRIPTION
SPARE PARTS	
SPARE - GENERIC	
IFS-1125C	Supervision module for monitored outputs for connection to relays
MW-03-048	BP-1-Annunciator Blank Spare Plate in APO Grey (for LST-816 / BC200)
PDM	Power Distribution Module. 8 x fused outputs, Door Holder Output
452-AUS	003 Key Lock for CAB650/CAB900 inc 1 key
SC085	10 Pack of Base Sounder Lids, white
SPARES - POWER SUPPLIES	
PBC-70	2.6 Amp 24V power supply to suit NPS-x (non-battery backed)
RSP-150-27	PS DC27V 150W with terminal cover
RSP-320-27	PS DC27V 320W with terminal cover
NPS-DISP	NPS-Display Display Kit for NPS-xxx
P87-6100-052	Spare Fuse holder w/Terminal - 250V 8Amp for PSU
SPARES - *** CONVENTIONAL FIRE ALARM CONTROL PANEL	
CFP-16/CPU	CPU\Termination Board Replacement for LST16
CFP-16/KEY	Keypad (AUS) & display for LST16
NPS-11CHS	NPS-11 Replacement to suit LST16
NPS-5CHS	NPS-5 Replacement to suit LST16
RLB-CFP-16	Replacement Lithium battery for LST16
SPARES - BC-200 SERIES FIRE ALARM CONTROL PANEL	
KEYPAD/00	Keypad Membrane to suit BC200 Keypad
BC200-CPU	BC-200 CPU & LCD display
PSI-AUS	Power Supply Interface to suit IFS-2600 + BC200
LCD-80AU	80 character LCD remote mimic panel to suit BC-200
SCS-8AU	Smoke Control Station with 8 x 3 position switches with 3 x LEDs per switch
SCS-8LAU	Custom mimic module 24 x inputs + 24 x outputs
ACM-16ATAUS/00	Annunciator Module with 16 Switches, 16 Red/Amber LEDs
ACM-32AAU	Annunciator Module with 32 Red LED E.g. Flow switches, monitors etc.
LDM-32/00	LED Driver card for Graphic Mimic - to suit BC-200
LDM-R32-AUS	Lamp driver relay kit 32 Relays (requires 10460 LDM-32). E.g. Plant & EWIS Interfaces
LIM	Loop Interface Module (IFS-725I), to suit BC-200
NIM	Network Interface Module (IFS-725I)
FIM	Termination Board, to suit BC-200
USB-AUS	USB to RS232 Converter, to suit BC-200, VESDA. Win7 Compatible

SAP PART #	DESCRIPTION
SPARES - SMX+ SERIES FIRE ALARM CONTROL PANEL	
CPU2-SMX+	CPU Assembly to suit FireLite SMX+
DISP-SMX+	Keypad replacement to suit SMX+/NCA-2
RLB-CFP-16	3V Lithium Battery Kit for CPU
BC200 TC ADDRESSABLE DETECTORS	
TC2700-W	HON CLIP Photo/ Opt.SmokeDet-Bright white
TC2700TMB-W	HON CLIP Acclim.MultiCrit.Det.-p.white
TC6500-W	HON CLIP Thermal Fix TypeDet-Bright whit
TC6500R-W	HON CLIP Therm.ROR Det-Bright white
TC6500R-W	HON CLIP Therm.ROR Det-Bright white

For More Information

T: 1300 246 247

E: sales@firex.com.au

W: www.firex.com.au