

50L AIR FOAM MOBILE EXTINGUISHER



SPECIFICATIONS

PRODUCT CODE	FXAFMOB50
CAPACITY	50 L
FIRE RATING	3A:20B *
AGENT	Tridol S 6% AFFF
OPERATING PRESSURE	1500 kPa
OVERALL MASS	79 kg
DISCHARGE DISTANCE	15 m
PRODUCT DIMENSIONS (H W D)	1300 mm X 595 mm X 590 mm
PRESSURE TEST	5 yearly
HOSE LENGTH	5 m
VALVE	Nickel coated Brass
CYLINDER	Stainless Steel, UV Powder Coat
TROLLEY	Steel, UV Powder Coat
TYRES	Pneumatic
APPROVALS	AS 4265

* 9.0L of this extinguishant has obtained a 3A:20B rating under test conditions for a portable extinguisher given in AS 1850.



APPLICATION

- Suitable for A Class Fires - (paper, wood, textiles)
- Suitable for B Class Fires - (flammable liquid fires such as oils, petrols and solvents)
- Dangerous if used on energised electrical equipment
- Appropriate for use in:
 - High coverage areas
 - Airports and remote airstrips
 - Fuel depots
 - Power stations
 - Mining sites
 - Marine terminals, offshore platforms
 - Motor race events
 - Rail / road loading facilities