

# 75L AIR FOAM MOBILE EXTINGUISHER

## SPECIFICATIONS



<b>PRODUCT CODE</b>	FXAFMOB75
<b>CAPACITY</b>	75 L
<b>FIRE RATING</b>	3A:20B *
<b>AGENT</b>	Tridol S 6% AFFF
<b>OPERATING PRESSURE</b>	1500 kPa
<b>OVERALL MASS</b>	117 kg
<b>DISCHARGE DISTANCE</b>	15 m
<b>PRODUCT DIMENSIONS (H W D)</b>	1300 mm X 595 mm X 690 mm
<b>PRESSURE TEST</b>	5 yearly
<b>HOSE LENGTH</b>	5 m
<b>VALVE</b>	Nickel coated Brass
<b>CYLINDER</b>	Stainless Steel, UV Powder Coat
<b>TROLLEY</b>	Steel, UV Powder Coat
<b>TYRES</b>	Pneumatic
<b>APPROVALS</b>	AS 4265

\* 9.0L of this extinguishant has obtained a 3A:20B rating under test conditions for a portable extinguisher given in AS 1850.



## APPLICATION

- Suitable for A Class Fires - (paper, wood, textiles)
- Suitable for B Class Fires - (flammable liquid fires such as oils, petrols and solvents)
- Dangerous if used on energised electrical equipment
- Appropriate for use in:
  - High coverage areas
  - Airports and remote airstrips
  - Fuel depots
  - Power stations
  - Mining sites
  - Marine terminals, offshore platforms
  - Motor race events
  - Rail / road loading facilities