## FIRE HOSE REEL SWIVEL ARM - 36 MTR



## **SPECIFICATIONS**



PRODUCT CODE	FXHRSA36
HOSE LENGTH &	36 m X 19 mm
INTERNAL DIAMETER	
HOSE CONSTRUCTION	Ribbed PVC
REEL PLATE DIAMETER	550 mm
INTERNAL WATERWAY	Galvanised Steel
SUPPORT ASSEMBLY	Zinc Plated Steel
INLET PIPE & UNION	Galvanised Steel
ISOLATION VALVE	Zinc coated Brass
HOSE GUIDE ARM	Zinc Plated
NOZZLE	Jet and Spray twist action
	Brass nozzle
WALL MOUNTING	Steel, Red Powder Coat
WALL MOUNTING BRACKET	Steel, Red Powder Coat
	Steel, Red Powder Coat  600 mm X 600 mm X 260
BRACKET	
BRACKET SHIPPING DIMENSIONS	600 mm X 600 mm X 260
BRACKET SHIPPING DIMENSIONS (H W D)	600 mm X 600 mm X 260 mm
BRACKET SHIPPING DIMENSIONS (H W D) OVERALL MASS	600 mm X 600 mm X 260 mm 22 kg
BRACKET SHIPPING DIMENSIONS (H W D) OVERALL MASS	600 mm X 600 mm X 260 mm 22 kg Isolation Valve with
BRACKET SHIPPING DIMENSIONS (H W D) OVERALL MASS	600 mm X 600 mm X 260 mm  22 kg Isolation Valve with nozzle retainer,
BRACKET SHIPPING DIMENSIONS (H W D) OVERALL MASS	600 mm X 600 mm X 260 mm  22 kg Isolation Valve with nozzle retainer, Male/Female Union
BRACKET SHIPPING DIMENSIONS (H W D) OVERALL MASS	600 mm X 600 mm X 260 mm  22 kg Isolation Valve with nozzle retainer, Male/Female Union Assembly, Hose Guide Arm and Wall Mounting Bracket
BRACKET SHIPPING DIMENSIONS (H W D) OVERALL MASS	600 mm X 600 mm X 260 mm  22 kg Isolation Valve with nozzle retainer, Male/Female Union Assembly, Hose Guide Arm and Wall





## **APPLICATION**

- Suitable for A Class Fires (paper, wood, textiles)
- Ideal for use in large high risk areas

