## 4.5KG ABE DRY CHEMICAL POWDER FIRE EXTINGUISHER



## SPECIFICATIONS

| PRODUCT CODE              | FXM45                 |
|---------------------------|-----------------------|
| CAPACITY                  | 4.5 kg                |
| FIRE RATING               | 4A:60B:E              |
| AGENT                     | 90% MAP Dry Chemical  |
|                           | Powder                |
| <b>OPERATING PRESSURE</b> | 1500 kPa              |
| DISCHARGE TIME            | 21 seconds            |
| PRODUCT DIMENSIONS        | 480 mm X 145 mm       |
| (H X CYL Ø)               |                       |
| CYLINDER THICKNESS        | 1.5 mm                |
| OVERALL MASS              | 7.2 kg                |
| CYLINDER                  | Steel, UV Powder Coat |
| HANDLE                    | Stainless Steel       |
| VALVE                     | Chrome plated Brass   |
| HOSE                      | EPDM, Brass ferrules  |
| HOSE RETAINER             | Stainless Steel       |
| APPROVALS                 | AS/NZS 1841.5         |
| SHIPPING DIMENSIONS       | 550 mm X 160 mm X 160 |
| (H W D)                   | mm                    |
| PALLET QTY                | 130                   |
| BRACKET SUPPLIED          | Wall Bracket          |
|                           |                       |





## **APPLICATION**

- Suitable for A Class Fires (paper, wood, textiles)
- Suitable for B Class Fires (flammable liquid fires such as oils, paints and solvents)
- Suitable for E Class Fires (energised electrical fires such as switch boards and electrical motors)

