

# 75KG ABE DRY CHEMICAL POWDER MOBILE EXTINGUISHER

## SPECIFICATIONS



<b>PRODUCT CODE</b>	FXPM0B75
<b>CAPACITY</b>	75 kg
<b>FIRE RATING</b>	6A:80B:E *
<b>AGENT</b>	90% MAP Dry Chemical Powder
<b>OPERATING PRESSURE</b>	1500 kPa
<b>OVERALL MASS</b>	117 kg
<b>DISCHARGE DISTANCE</b>	18 m
<b>PRODUCT DIMENSIONS (H W D)</b>	1300 mm X 595 mm X 690 mm
<b>PRESSURE TEST</b>	5 yearly
<b>HOSE LENGTH</b>	5 m
<b>VALVE</b>	Nickel coated Brass
<b>CYLINDER</b>	Stainless Steel, UV Powder Coat
<b>TROLLEY</b>	Steel, UV Powder Coat
<b>TYRES</b>	Pneumatic
<b>APPROVALS</b>	AS 4265

\* 9.0kg of this extinguishant has obtained a 6A:80B:E rating under test conditions for a portable extinguisher given in AS 1850.



## APPLICATION

- Suitable for A Class Fires (paper, wood, textiles)
- Suitable for B Class Fires (flammable liquid fires such as oils, paints and solvents)
- Suitable for E Class Fires (energised electrical fires such as switch boards and electrical motors)
- Appropriate for use in:
  - High coverage areas
  - Remote airstrips where access to water is limited
  - Small fuel storage areas
  - Mining sites
  - Manufacturing plants
  - Large storage facilities