

## 9.0L AIR FOAM FIRE EXTINGUISHER



## **SPECIFICATIONS**

| PRODUCT CODE        | FXAF                  |
|---------------------|-----------------------|
| CAPACITY            | 9.0 L                 |
| FIRE RATING         | 3A:20B                |
| AGENT               | Tridol S 6% AFFF      |
| OPERATING PRESSURE  | 1000 kPa              |
| DISCHARGE TIME      | 45 seconds            |
| PRODUCT DIMENSIONS  | 630 mm X 180 mm       |
| (H X CYL Ø)         |                       |
| OVERALL MASS        | 12.5 kg               |
| CYLINDER            | Stainless Steel, UV   |
|                     | Powder Coat           |
| HANDLE              | Stainless Steel       |
| VALVE               | Chrome plated Brass   |
| HOSE                | EPDM                  |
| APPROVALS           | AS/NZS 1841.4         |
| SHIPPING DIMENSIONS | 660 mm X 200 mm X 190 |
| (H W D)             | mm                    |
| PALLET QTY          | 58                    |
| BRACKET SUPPLIED    | Wall Bracket          |
|                     |                       |



## APPLICATION

Certified Product

- Suitable for A Class Fires (paper, wood, textiles)
- Suitable for B Class Fires (flammable liquid fires such as oils, petrols and solvents)
- Dangerous if used on energised electrical equipment

